




Feature

- High light efficiency ≥ 110 lm/w
- High Color Rendering Index (CRI) ≥ 80
- High Power Factor (PF) ≥ 0.95
- Longer life span ≥ 50000 hrs.
- Beam angle 160 degree, perfect lighting effect and best color uniform



Dimension

Specifications

General Informations		Operating Temp.	
Product Name	NEX Illumi T8-09	Operating Humi.	-20°C to 50°C
Rated Power	9W	Lifespan	10% to 90%
LED Type	SMD	Warranty	50000 Hrs.
Luminous Efficiency	≥ 110 lm/W		3 Years*
Luminous Flux	≥ 1000 Lumen	Electrical Informations	
Color Temp.	Warm white (3000 $\pm$ 300K)	Driver	Non-isolated
	Natural white (4000 $\pm$ 400K)	Input Voltage	AC85-265V
	Cool white (6500 $\pm$ 500K)	Frequency	50/60Hz
CRI (Ra)	≥ 80	Input type	Double-end
Beam Angle	160D	Power Factor	≥ 0.95
IP Protection	IP20	Total Harmonic (THDi)	$\leq 5\%$
Replacement	18W Fluorescent tube	Certificates & Test reports	
Dimensions	$\varnothing 30 \times 598$ mm	Certificates	CE, RoHS, TISI
Lamp Base	G13	Test Reports	LM80/TM21
Cap Type	Adjustable angle		
Weight	150 g.		
Housing Material	Aluminum & PC cover		
Cover Type	Milky		

Remark: The information contained in this document is subject to change without notice.
* 18Hrs/Day



NEX Office & Showroom

Sookkamol Ratchada Building 2Floor,
410/17-23 Ratchadaphisek Rd., Samsennok,
Huay Kwang, Bangkok 10310, THAILAND

Tel. +662 204 7565
Fax. +662 938 3672
Email: info@nexledtech.com

www.nexledtech.com
www.nexinnotech.com

Ref. NEX Illumi T8-XX V190620-3