




Features

- High light efficiency ≥ 110 Lm/w
- High Color Rendering Index (CRI) ≥ 80
- High Power Factor (PF) > 0.98
- Longer life span ≥ 50000 hrs.
- Beam Angle 160 degree, perfect lighting effect and best color uniform



Dimension


Specifications

General Informations		Electrical Informations	
Product Name	NEX Endura T8-09	Driver	Included driver
Rated Power	9W	Input Voltage	AC85-265V
Luminous Efficiency	≥ 110 Lm/W	Frequency	50/60Hz
Luminous Flux	≥ 1000 Lumen	Input Type	Double-end
Color Temp.	Warm white(3000K $\pm$ 300) Natural white (4500K $\pm$ 400) Cool white (6500K $\pm$ 500)	Power Factor	> 0.98
CRI (Ra)	≥ 80	Total Harmonic (THDi)	$< 5\%$
UV	No UV	Surge Protection	$> 3kV$
Beam Angle	160 Deg.	Light Fricker	Flicker free
IP Protection	IP20	Certificates & Test reports	
Replacement	T8 18W Fluorescent tube		
Lamp Base	G13	Certificates	CE, RoHS, TISI
Dimensions	W30 x L598 mm	Test Reports	LM80/TM21
Weight	150 g.	Remark: The information contained in this document is subject to change without notice. * 18Hrs/Day	
Housing Material	Aluminum AL6063		
Cover Type	Milky		
Operating Temp.	-20°C to 45°C		
Operating Humi.	10% to 90%		
Lifespan	50000 Hrs.		
Warranty	3 Years*		



Features

- High light efficiency ≥ 115 Lm/w
- High Color Rendering Index (CRI) ≥ 80
- High Power Factor (PF) > 0.98
- Longer life span ≥ 50000 hrs.
- Beam Angle 160 degree, perfect lighting effect and best color uniform



Dimension

Specifications

General Informations		Electrical Informations	
Product Name	NEX Endura T8-18	Driver	Included driver
Rated Power	18W	Input Voltage	AC85-265V
Luminous Efficiency	≥ 115 Lm/W	Frequency	50/60Hz
Luminous Flux	≥ 2100 Lumen	Input Type	Double-end
Color Temp.	Warm white(3000K $\pm$ 300) Natural white (4500K $\pm$ 400) Cool white (6500K $\pm$ 500)	Power Factor	> 0.98
CRI (Ra)	≥ 80	Total Harmonic (THDi)	$< 5\%$
UV	No UV	Surge Protection	$> 3kV$
Beam Angle	160 Deg.	Light Fricker	Flicker free
IP Protection	IP20	Certificates & Test reports	
Replacement	T8 36W Fluorescent tube		
Lamp Base	G13	Certificates	CE, RoHS, TISI
Dimensions	W30 x L1198 mm	Test Reports	LM80/TM21
Weight	220 g.	Remark: The information contained in this document is subject to change without notice. * 18Hrs/Day	
Housing Material	Aluminum AL6063		
Cover Type	Milky		
Operating Temp.	-20°C to 45°C		
Operating Humi.	10% to 90%		
Lifespan	50000 Hrs.		
Warranty	3 Years*		