




Dimension



Applications



Specifications

General Informations	
Product Name	NEX Enova T5-09
Rated Power	9W
Luminous Efficiency	≥110 lm/W
Luminous Flux	≥990 lumen
Color Temp.	Warm white (3000K±300) Natural white (4000K±400) Cool white (6000K±500)
CRI (Ra)	≥80
Beam Angle	140 Deg.
IP Protection	IP20
Replacement	T5 14W Fluorescent tube
Lamp Base	G5
Dimensions	W219 x L574 mm
Weight	120 g.
Housing Material	Aluminum AL6063
Operating Temp.	-40°C to 45°C
Operating Humi.	10% to 90%
Lifespan	50,000 Hrs.
Warranty	3 Years*

Electrical Informations	
Driver	Included driver
Input Voltage	AC85-265V
Frequency	50/60Hz
Input Type	Double-end
Power Factor	≥0.90
Total Harmonic (THDi)	≤10%
Surge Protection	>2kV
Light Fricker	Fricker free


Certificates & Test Reports	
Certificates	CE, RoHS, TISI
Test Reports	LM80/TM21, LM79

Remark: The information contained in this document is subject to change without notice.
* 18Hrs/Day





Dimension



Applications



Specifications

General Informations

Product name	NEX Enova T5-18
Rated power	18W
Luminous efficiency	≥115 Lm/W
Luminous flux	≥2160 Lumen (6000K)
Color temp.	Warm white (3000K±300) Natural white (4000K±400) Cool white (6000K±500)
CRI (Ra)	≥80
Beam angle	140 Deg.
IP protection	IP20
Replacement	T5 28W Fluorescent tube
Lamp base	G5
Dimensions	W219 x L1148 mm
Weight	190 g.
Housing material	Aluminum AL6063
Operating temp.	-40°C to 45°C
Operating humi.	10% to 90%
Lifespan	50,000 Hrs.
Warranty	3 Years*

Electrical Informations

Driver	Included driver
Input voltage	AC85-265V
Frequency	50/60Hz
Input type	Double-end
Power factor	≥0.90
Total harmonic (THD)	≤10%
Surge protection	>2kV
Light fricker	Fricker free

Certificates & Test reports

Certificates	CE, RoHS, TISI
Test reports	LM80/TM21, LM79

Remark: The information contained in this document is subject to change without notice.
* 18Hrs/Day

