




Features

- High Color Rendering Index (CRI) ≥ 80
- High Power Factor (PF) > 0.95
- Longer life span ≥ 50000 hrs.
- Beam Angle 45 degree, perfect lighting effect and best color uniform



Dimension

Specifications

General Informations	
Product Name	NEX Alpha
Rated Power	14W
Luminous Flux	≥ 1450 lumen
Color Temp.	Natural white (4000K $\pm$ 400) Cool white (6500K $\pm$ 500)
CRI (Ra)	≥ 80
UV	No UV
Beam Angle	45D
IP Protection	IP20
Dimensions	W23xH30xL1200 mm
Weight	398g
Lamp Base	G13
Replacement	T8 36W Fluorescent tube
Housing Material	Aluminum
Operating Temp.	-20°C to 45°C
Operating Humi.	10% to 90%
Life Span	50000 Hrs.
Warranty	3 Years*

Electrical Informations	
Driver	Included driver
Input Voltage	AC85-265V
Frequency	50/60Hz
Input Type	Double-end
Power Factor	> 0.95
Total Harmonic (THDi)	$< 10\%$
Surge Protection	$> 2kV$
Light Fricker	Flicker free

Certificates & Test reports	
Certificates	CE, RoHS, TISI
Test Reports	LM80/TM21


Remark: The information contained in this document is subject to change without notice.
* 18Hrs/Day





Features

- High Color Rendering Index (CRI) ≥ 80
- High Power Factor (PF) > 0.95
- Longer life span ≥ 50000 hrs.
- Beam Angle 45 degree, perfect lighting effect and best color uniform



Dimension

Specifications

General Informations	
Product Name	NEX Alpha
Rated Power	22W
Luminous Flux	≥ 1950 lumen
Color Temp.	Natural white (4000K $\pm$ 400) Cool white (6500K $\pm$ 500)
CRI (Ra)	≥ 80
UV	No UV
Beam Angle	45D
IP Protection	IP20
Dimensions	W23xH30xL1200 mm
Weight	398g
Lamp Base	G13
Replacement	T8 36W Fluorescent tube
Housing Material	Aluminum
Operating Temp.	-20°C to 45°C
Operating Humi.	10% to 90%
Life Span	50000 Hrs.
Warranty	3 Years*

Electrical Informations	
Driver	Included driver
Input Voltage	AC85-265V
Frequency	50/60Hz
Input Type	Double-end
Power Factor	> 0.95
Total Harmonic (THDi)	$< 10\%$
Surge Protection	$> 2kV$
Light Fricker	Flicker free

Certificates & Test reports	
Certificates	CE, RoHS, TISI
Test Reports	LM80/TM21


Remark: The information contained in this document is subject to change without notice.
* 18Hrs/Day





Features

- High Color Rendering Index (CRI) ≥ 80
- High Power Factor (PF) > 0.95
- Longer life span ≥ 50000 hrs.
- Beam Angle 45 degree, perfect lighting effect and best color uniform



Dimension

Specifications

General Informations		Electrical Informations	
Product Name	NEX Alpha	Driver	Included driver
Rated Power	25W	Input Voltage	AC85-265V
Luminous Flux	≥ 2030 lumen	Frequency	50/60Hz
Color Temp.	Natural white (4000K $\pm$ 400) Cool white (6500K $\pm$ 500)	Input Type	Double-end
CRI (Ra)	≥ 80	Power Factor	> 0.95
UV	No UV	Total Harmonic (THDi)	$< 10\%$
Beam Angle	45D	Surge Protection	$> 2kV$
IP Protection	IP20	Light Fricker	Flicker free
Dimensions	W23xH30xL1200 mm	Certificates & Test reports	
Weight	398g	Certificates	CE, RoHS, TISI
Lamp Base	G13	Test Reports	LM80/TM21
Replacement	T8 36W Fluorescent tube	Remark: The information contained in this document is subject to change without notice. * 18Hrs/Day	
Housing Material	Aluminum		
Operating Temp.	-20°C to 45°C		
Operating Humi.	10% to 90%		
Life Span	50000 Hrs.		
Warranty	3 Years*		