




### Features

- High Color Rendering Index (CRI)  $\geq 80$
- High Power Factor (PF)  $> 0.95$
- Longer life span  $\geq 50000$  hrs.
- Beam Angle 45 degree, perfect lighting effect and best color uniform



Dimension


### Specifications

| General Informations |                                                                 | Electrical Informations                                                                                |                 |
|----------------------|-----------------------------------------------------------------|--------------------------------------------------------------------------------------------------------|-----------------|
| Product Name         | NEX Alpha                                                       | Driver                                                                                                 | Included driver |
| Rated Power          | 14W                                                             | Input Voltage                                                                                          | AC85-265V       |
| Luminous Flux        | $\geq 1340$ lumen                                               | Frequency                                                                                              | 50/60Hz         |
| Color Temp.          | Natural white (4000K $\pm$ 400)<br>Cool white (6500K $\pm$ 500) | Input Type                                                                                             | Double-end      |
| CRI (Ra)             | $\geq 80$                                                       | Power Factor                                                                                           | $> 0.95$        |
| UV                   | No UV                                                           | Total Harmonic (THDi)                                                                                  | $< 10\%$        |
| Beam Angle           | 45D                                                             | Surge Protection                                                                                       | $> 2kV$         |
| IP Protection        | IP20                                                            | Light Fricker                                                                                          | Flicker free    |
| Dimensions           | W23xH30xL1170 mm                                                | Certificates & Test reports                                                                            |                 |
| Weight               | 398g                                                            | Certificates                                                                                           | CE, RoHS, TISI  |
| Lamp Base            | G5                                                              | Test Reports                                                                                           | LM80/TM21       |
| Replacement          | T5 36W Fluorescent tube                                         | Remark: The information contained in this document is subject to change without notice.<br>* 18Hrs/Day |                 |
| Housing Material     | Aluminum                                                        | <div> </div>                                                                                           |                 |
| Operating Temp.      | -20°C to 45°C                                                   |                                                                                                        |                 |
| Operating Humi.      | 10% to 90%                                                      |                                                                                                        |                 |
| Life Span            | 50000 Hrs.                                                      |                                                                                                        |                 |
| Warranty             | 3 Years*                                                        |                                                                                                        |                 |



### Features

- High Color Rendering Index (CRI)  $\geq 80$
- High Power Factor (PF)  $> 0.95$
- Longer life span  $\geq 50000$  hrs.
- Beam Angle 45 degree, perfect lighting effect and best color uniform



Dimension

### Specifications

| General Informations |                                                                 | Electrical Informations                                                                                |                 |
|----------------------|-----------------------------------------------------------------|--------------------------------------------------------------------------------------------------------|-----------------|
| Product Name         | NEX Alpha                                                       | Driver                                                                                                 | Included driver |
| Rated Power          | 30W                                                             | Input Voltage                                                                                          | AC85-265V       |
| Luminous Flux        | $\geq 2800$ lumen                                               | Frequency                                                                                              | 50/60Hz         |
| Color Temp.          | Natural white (4000K $\pm$ 400)<br>Cool white (6500K $\pm$ 500) | Input Type                                                                                             | Double-end      |
| CRI (Ra)             | $\geq 80$                                                       | Power Factor                                                                                           | $> 0.95$        |
| UV                   | No UV                                                           | Total Harmonic (THDi)                                                                                  | $< 10\%$        |
| Beam Angle           | 45D                                                             | Surge Protection                                                                                       | $> 2kV$         |
| IP Protection        | IP20                                                            | Light Fricker                                                                                          | Flicker free    |
| Dimensions           | W23xH30xL1170 mm                                                | Certificates & Test reports                                                                            |                 |
| Weight               | 398g                                                            | Certificates                                                                                           | CE, RoHS, TISI  |
| Lamp Base            | G5                                                              | Test Reports                                                                                           | LM80/TM21       |
| Replacement          | T5 36W Fluorescent tube                                         | Remark: The information contained in this document is subject to change without notice.<br>* 18Hrs/Day |                 |
| Housing Material     | Aluminum                                                        | <div> </div>                                                                                           |                 |
| Operating Temp.      | -20°C to 45°C                                                   |                                                                                                        |                 |
| Operating Humi.      | 10% to 90%                                                      |                                                                                                        |                 |
| Life Span            | 50000 Hrs.                                                      |                                                                                                        |                 |
| Warranty             | 3 Years*                                                        |                                                                                                        |                 |