




Features



Color Temp. Selectable

• 3000K
• 4000K
• 5700K



Rated Power Selectable

• 10W
• 13W
• 16W



Size Adjustable for Cut Hole

65mm/2.5Inc	115mm/4.5Inc	165mm/6.5Inc
78mm/3.0Inc	130mm/5.0Inc	180mm/7.0Inc
90mm/3.5Inc	140mm/5.5Inc	190mm/7.5Inc
102mm/4.0Inc	155mm/6.0Inc	205mm/8.0Inc

Specifications

General Informations

Product Name	NEX Uniflex
Rated Power	10W/13W/16W
Luminous Flux	900/1300/1800 lumen
Color Temp.	WW/CW/DL Selectable (3000K/4000K/5700K)
CRI (Ra)	≥80
Beam Angle	90D
IP Protection	IP20
Installation Type	Surface mounted
Dimensions	Ø235x20mm
Cut Hole	65-205mm
Weight	410g
Housing Material	PC
Housing Color	White
Operating Temp	-20°C to 45°C
Operating Humi.	10% To 90%
Life Span	>50000 Hrs.
Warranty	3 Years*

Electrical Informations

Driver	Included
Input Voltage	AC200-240V
Frequency	50/60Hz
Power Factor	≥0.90
Total Harmonic(THDi)	≤20%
Surge Protection	>0.5kV
Dimmable	No

Certificates & Test reports

Certificates	CE, RoHS, TISI
Test Reports	LM80/TM21

Remark: The information contained in this document is subject to change without notice.
* 18Hrs/Day

CE RoHS

