


## LED Canopy Light 35W



≥3850Lm

CRI≥80

PF 0.99

### Features

- Patented passive cooling solution to manage surface temperature rising of luminaire at 30°C, junction temperature of led chip controlled at 90°C.
- Optical glass led lens with a light transmission more than 93%, offering the least light output loss, special rectangle shape designed to have a symmetric beam patter.
- 50000 hours lifespan putting the luminaire replacement circle to 20 years.
- Power factor at 0.99.
- 3 years warranty

### Specifications

|                            |                                                     |                                       |                |
|----------------------------|-----------------------------------------------------|---------------------------------------|----------------|
| <b>Product Name</b>        | Enova CN-35                                         | <b>Dimension</b>                      | 300x300mm      |
| <b>Rated Power</b>         | 35W                                                 | <b>Net Weight</b>                     | 2.8 kg         |
| <b>LED Efficiency</b>      | ≥140Lm/W                                            | <b>Replacement</b>                    | 70W-100W HID   |
| <b>Luminous Efficiency</b> | ≥110Lm/W                                            | <b>Material</b>                       | Aluminum Alloy |
| <b>Luminous Flux</b>       | ≥3850Lm                                             | <b>Material of Lens</b>               | Optical glass  |
| <b>Color Temp.</b>         | Warm white (3000K±300)<br>Natural white (5000K±500) | <b>Light Transmission of LED Lens</b> | ≥93%           |
| <b>CRI</b>                 | ≥80                                                 | <b>Operating Temp.</b>                | -25°C to 45°C  |
| <b>Beam Angle</b>          | 45°/ 60°/ 85°/ 120°                                 | <b>Operating Humi.</b>                | 10% to 90%     |
| <b>Input Voltage</b>       | AC 180-260V                                         | <b>Certificate</b>                    | CE, RoHS       |
| <b>Frequency</b>           | 50/60Hz                                             | <b>Life Span</b>                      | ≥50000Hrs.     |
| <b>Output Current</b>      | 0.16A                                               | <b>Warranty</b>                       | 3 Years*       |
| <b>Power Factor</b>        | 0.99                                                |                                       |                |
| <b>Power Efficiency</b>    | ≥86%                                                |                                       |                |
| <b>Harmonic (THD)</b>      | ≤7%                                                 |                                       |                |

Remark: The information contained in this document is subject to change without notice. \*18Hrs/Day

CE RoHS

### NEX Office

#### Singapore

50 Raffles Place, #37-00 Singapore Land  
Tower 048623 Singapore  
Tel.: (+65) 6829 7014 Fax.: (+65) 6829 707

Email: [info@nexledtec.com](mailto:info@nexledtec.com) [www.nexledtec.com](http://www.nexledtec.com)

#### Taiwan

4F, No.105 Zhongcheng Rd., Tucheng Distric,  
New Taipei City 23674 Taiwan  
Tel.: 886-2-22697815 Fax.: 886-2-22697807

#### Thailand

Q House Lumpini, 1 South Sathorn Rd., 27F,  
Tungmahamek, Sathorn, Bangkok 10120 Thailand  
Tel.&Fax.: +662 938 3672