


Cutting Size
75-80mm



1M	768Lx	0.7M
2M	192Lx	1.4M
3M	85Lx	2.2M
4M	48Lx	2.9M
5M	30Lx	3.7M

Height E Angle: 48.3 Deg Dia.

Features

High color rendering, uniform luminance, no light spot, no dark space. It was different from the lighting effects of general LED DOWNLIGHT in the market, substitute to the traditional lamp completely, and no maladjustment

Applications

Products are widely used as indoor main illumination lighting in the office, commercial center, shopping mall, supermarket, factory, etc.

Specification

Product Name	Illumi DL-08
LED Power	6W
Rated Power	7.5W
Luminous Flux	≥600Lm
Color Temp.	Warm white (3000K±200)
CRI	≥80
Beam Angle	30°
Input Voltage	AC 100-240V
Frequency	50/60Hz
Current	320mA
Dimmable	No

Dimension	Ø90x75mm
Material	Aluminum & PC cover
Cover Material	Clear
Weight	260g
Operating Temp.	-20°C to 50°C
Operating Humi.	10% to 90%

Certificate	CE, RoHS, TISI
Life Span	≥50000Hrs.
Warranty	3 Years*

Remark: The information contained in this document is subject to change without notice.*18Hrs/Day



NEX Office

Singapore

50 Raffles Place, #37-00 Singapore Land
Tower 048623 Singapore
Tel.: (+65) 6829 7014 Fax.: (+65) 6829 707

Email: info@nexledtec.com www.nexledtec.com

Taiwan

4F, No.105 Zhongcheng Rd., Tucheng Distric,
New Taipei City 23674 Taiwan
Tel.: 886-2-22697815 Fax.: 886-2-22697807

Thailand

Q House Lumpini, 1 South Sathorn Rd., 27F,
Tungmahamek, Sathorn, Bangkok 10120 Thailand
Tel.&Fax.: +662 938 3672