


COB




Features

High color rendering, uniform luminance, no light spot, no dark space. It was different from the lighting effects of general LED DOWNLIGHT in the market, substitute to the traditional lamp completely, and no maladjustment



Application

Products are widely used as indoor main illumination lighting in the office, commercial center, shopping mall, supermarket, factory, etc.



1M	5325Lx	0.7M
2M	1331Lx	1.4M
3M	591Lx	2.2M
4M	332Lx	2.9M
5M	213Lx	3.7M

Hight E Angle: 48.62 Deg Dia.



Cutting Size
200-220mm

Specification

Product Name	Illumi DL-50COB	Frequency	50/60Hz
Rated Power	50W	Power Factor	≥0.9
Color Temp.	Warm white (3000±300K)	Power Efficiency	≥87%
	Natural white (4000±400K)	Dimmable	No (Yes Option)
	Cool white (6000±500K)	IP Grade	IP33
Luminous Flux	≥4600Lm (Warm white)	Dimension	Ø230x120mm
	≥4700Lm (Natural white)	Cutting Size	200-220mm
	≥4800Lm (Cool white)	Housing Color	Aluminum (White, Black)
Beam Angle	40°	Weight	2200g
CRI	≥80	Operating Temp.	-40°C to 55°C
Driver	Include	Certificate	CE, RoHS, UL, FCC, SAA,
Current	1050mA	Life Span	≥50000 Hrs.
Input Voltage	AC 85-265V	Warranty	3 Years*

Remark: The information contained in this document is subject to change without notice. *18Hrs/Day

NEX Office

Singapore

50 Raffles Place, #37-00 Singapore Land
Tower 048623 Singapore
Tel.: (+65) 6829 7014 Fax.: (+65) 6829 707

Email: info@nexledtec.com www.nexledtec.com

Taiwan

4F, No.105 Zhongcheng Rd., Tucheng Distric,
New Taipei City 23674 Taiwan
Tel.: 886-2-22697815 Fax.: 886-2-22697807

Thailand

Q House Lumpini, 1 South Sathorn Rd., 27F,
Tungmahamek, Sathorn, Bangkok 10120 Thailand
Tel.&Fax.: +662 938 3672