


LED Surface-mounted downlight SMD-R04




Description


LED Surface-mounted downlight: SMD-R04 are originally researched and developed by NEX, die-casting high-rank aluminum integrated heat sink, international top COB CITIZEN chip, PET reflector, mirror-finish anodized, reflective rate>95% , high grade glass, transparent rate>93%, with high quality driver, stable specifications, glare free, good heat sink, brilliant quality, more than 40,000 hours life span.

Features


- High Ra>80, Low SDCM<3
- High efficacy, high illuminance
- Glare-free design, perfect light spot and accurate beam angle, make surroundings of comfortable illumination
- Refined components and design, guarantee a long life span of over 40,000 hours
- User-centered installation design, convenient and simple use



Beam Angle=40°



Beam Angle=40°



Beam Angle=40°

Specifications

General Informations

Product name	NEX Neolux SMD-R04
Rated power	25W
Luminous flux	2790Lm-2800Lm (3000K) 2900Lm-3080Lm (4000K) 2910Lm-2960Lm (5000K)
Color temp.	Warm white (3000K+300) Natural white (4000K+400) Cool white (5000K+500)
CRI (Ra)	≥80
Beam angle	15D/24D/40D/60D
IP protection	IP20
Replacement	50W-75W Traditional lamp
Dimensions	Ø105 x H200 mm
Gross weight	0.90 Kg.
Housing material	Aluminum Alloy
Housing color	Black/White/Silver

Operating temp.	-20DC to 50DC
Operating humi.	10% to 90%
Lifespan	40,000 Hrs.
Warranty	3 Years*

Electrical Informations

Input voltage	AC200-240V
Frequency	50/60Hz
Dimmable	No
Power factor	≥0.90

Certificates & Test reports

Certificates	CE, RoHS, TISI
Test reports	LM80/ TM21

Remark: The information contained in this document is subject to change without notice.
* 18Hrs/Day



NEX Office & Showroom

Sookkamol Ratchada Building 2Floor,
410/17-23 Ratchadaphisek Rd., Samsennok,
Huay Kwang, Bangkok 10310, THAILAND

Tel. +662 204 7565
Fax. +662 938 3672
Email: info@nexledtech.com

www.nexledtech.com
www.nexinnotech.com