<image><complex-block><complex-block>

Features

High color rendering, uniform luminance, no light spot, no dark space. It was different from the lighting effects of general LED DOWNLIGHT in the market, substitute to the traditional lamp completely, and no maladjustment

Application

Products are widely used as indoor main illumination lighting in the office, commercial center, shopping mall, supermarket, factory, etc.

LED Lamp specification

Product Name Rated Power LED Power Luminous Efficiency Luminous Flux Color Temp. CRI Beam Angle Input Voltage Frequency Illumi DL-35 COB 35W 30W ≥100Lm/W ≥3500Lm Warm white (3000±300K) ≥80 25° AC100-277V Dimension Material Surface Color Installation Operating Temp. Operating Humi.

Certificate Life Span Warranty Ø130xH162mm Aluminum Silver, Black Surface mount -20°C to 50°C 10% to 90%

CE,RoHS ≥50000Hrs. 3 Years*

Remark: The information contained in this document is subject to change without notice. *18Hrs/day

50/60Hz

≥0.90

NEX Office

Power Factor

 Singapore
 Taiw

 50 Raffles Place, #37-00 Singapore Land
 4F, N

 Tower 048623 Singapore
 New

 Tel.: (+65) 6829 7014
 Fax.: (+65) 6829 707
 Tel.: 4

 Email: info@nexledtec.com
 www.nexledtec.com

Taiwan

4F, No.105 Zhongcheng Rd., Tucheng Distric, New Taipei City 23674 Taiwan Tel.: 886-2-22697815 Fax.: 886-2-22697807

Thailand

Q House Lumpini, 1 South Sathorn Rd., 27F, Tungmahamek, Sathorn, Bangkok 10120 Thailand Tel.&Fax.: +662 938 3672