


Features

- High brightness, Low SDCM < 3, low light decline
- The use of lens and reflector combination of optical systems
- Refined components and design, guarantee a long life span of over 40,000 hours
- Exterior driver triac dimmable (200-240v input) and 1-10v Dimmable (100-240v input)

Dimensions (Unit: mm)



CITIZEN COB



SDCM <3



11W/2*11W



Color Black/White



24°



120*120/230*120




AC100-240/
220-240V 50/60Hz




3 YEAR 3 Years Warranty


Photometric diagram




11W 24° 3000K CRI>90



11W 24° 4000K CRI>90



2*11W 24° 3000K CRI>90



2*11W 24° 4000K CRI>90

Order Information

Model	Power	LED Current	CCT	Luminous Flux	CRI	PF
NX-NOL-GLI11-9030-1C04-24XY	11W	260mA	3000K	812lm	90	≥0.9
NX-NOL-GLI11-9040-1C04-24XY	11W	260mA	4000K	857lm	90	≥0.9
NX-NOL-GLI22-9030-2C04-24XY	2*11W	520mA	3000K	1668lm	90	≥0.95
NX-NOL-GLI22-9040-2C04-24XY	2*11W	520mA	4000K	1827lm	90	≥0.95

Remark: X=F(ON-OFF) X=A(1-10V) X=T(Triac Dim) X=D(Dali Dim) X=N(Without Driver) Y=B(Black) Y=W(White)



NEX Office & Showroom

Sookkamol Ratchada Building 2Floor,
410/17-23 Ratchadaphisek Rd., Samsennok,
Huay Kwang, Bangkok 10310, THAILAND

Tel. +662 204 7565
Fax. +662 938 3672
Email: info@nexledtech.com

www.nexledtech.com
www.nexinnotech.com