



≥13500Lm

PF≥0.95



5m	68Lx	151cm
6m	47Lx	181cm
8m	26Lx	241cm
10m	17Lx	301cm
12m	12Lx	361cm
Height	E	Diameter

Features

- Unique "Patented" Sunflower Heat Sink™ Thermal Dissipation.
- Utilizes High Brightness LEDs, >70CRI
- Easily Accessible High Efficiency Meanwell IP65 Power Supply.
- Light Weight but Rugged Die-cast Aluminum Housing (No maintenance required).
- Anti-corrosion Coating Surface and Wholly IP65 Design Suitable for All Kinds of Weather.
- High Reflectance Reflector Reccessed in the Luminaries Features One-piece Design.
- System Rating is 50,000hrs(70% lumen maintenance).

Specification

Model	Apollo HB120	Dimmable	☐ No ☐ Yes (Option)
Rated Power	120W	IP Protection	IP65
LED Chip	Nichia	Dimension	Ø360x229.5mm
Lighting Efficiency	≥110Lm/W	Material	Aluminum alloy
Luminous Flux	≥13500Lm	Weight	5.8 KGS
Color Temp.	☐ 3000K ☐ 4000K ☐ 5000K ☐ 6000K	Color	☐ White ☐ Black
CRI	☐ 70 ☐ 80 ☐ 90	Operating Temp.	-30°C to 50°C
Beam Angle	120°	Operating Humi.	10% to 90%
Input Voltage	100-277 VAC	Certificate	CE, RoHS
Frequency	50/60Hz	Life span	≥50000Hrs.
Power Factor	≥0.95	Suggested Usage	24 Hrs/Day
Harmonic (THD)	<15%	Warranty	5 Years

Remark: The information contained in this document is subject to change without notice. CCT±300K

NEX Office

Singapore

50 Raffles Place, #37-00 Singapore Land
Tower 048623 Singapore
Tel.: (+65) 6829 7014 Fax.: (+65) 6829 707

Email: info@nexledtec.com www.nexledtec.com

Taiwan

4F, No.105 Zhongcheng Rd., Tucheng Distric,
New Taipei City 23674 Taiwan
Tel.: 886-2-22697815 Fax.: 886-2-22697807

Thailand



Q House Lumpini, 1 South Sathorn Rd., 27F,
Tungmahamek, Sathorn, Bangkok 10120 Thailand
Tel.&Fax.: +662 938 3672

NEX Apollo

LED High Bay 180W

≥19200Lm

PF≥0.95



5m	96Lx	151cm
6m	67Lx	181cm
8m	38Lx	241cm
10m	24Lx	312cm
12m	17Lx	362cm
Height	E	Diameter

Features

- Unique "Patented" Sunflower Heat Sink™ Thermal Dissipation.
- Utilizes High Brightness LEDs, >70CRI
- Easily Accessible High Efficiency Meanwell IP65 Power Supply.
- Light Weight but Rugged Die-cast Aluminum Housing (No maintenance required).
- Anti-corrosion Coating Surface and Wholly IP65 Design Suitable for All Kinds of Weather.
- High Reflectance Reflector Reccessed in the Luminaries Features One-piece Design.
- System Rating is 50,000hrs(70% lumen maintenance).

Specification

Model	Apollo HB180	Dimmable	☐ No ☐ Yes (Option)
Rated Power	180W	IP Protection	IP65
LED Chip	Nichia	Dimension	Ø360x236mm
Lighting Efficiency	≥110Lm/W	Material	Aluminum alloy
Luminous Flux	≥19200Lm	Weight	6.6 KGS
Color Temp.	☐ 3000K ☐ 4000K ☐ 5000K ☐ 6000K	Color	☐ White ☐ Black
CRI	☐ 70 ☐ 80 ☐ 90	Operating Temp.	-30°C to 50°C
Beam Angle	120°	Operating Humi.	10% to 90%
Input Voltage	100-277 VAC	Certificate	CE, RoHS
Frequency	50/60Hz	Life span	≥50000Hrs.
Power Factor	≥0.95	Suggested Usage	24 Hrs/Day
Harmonic (THD)	<15%	Warranty	5 Years

Remark: The information contained in this document is subject to change without notice. CCT±300K

NEX Office

Singapore

50 Raffles Place, #37-00 Singapore Land
Tower 048623 Singapore
Tel.: (+65) 6829 7014 Fax.: (+65) 6829 707

Email: info@nexledtec.com www.nexledtec.com

Taiwan

4F, No.105 Zhongcheng Rd., Tucheng Distric,
New Taipei City 23674 Taiwan
Tel.: 886-2-22697815 Fax.: 886-2-22697807

Thailand

Q House Lumpini, 1 South Sathorn Rd., 27F,
Tungmahamek, Sathorn, Bangkok 10120 Thailand
Tel.&Fax.: +662 938 3672