



≥44000Lm

CRI≥80

PF≥0.95

Features

- Fin shape heat sink with surface area for cooling up to 5000mm² per watt, to make sure no overheat of LED, Junction temperature controlled around 100°C (Junction temperature capacity up to 140°C)
- High performance and durable power supply: Main components are imported. Efficiency factor up to 0.9, power factor at ≥0.95, multiple protections: Short circuit / Over load/ Over voltage/ Over temp.
- Detachable: LED part and power supply part is Separable and Replaceable. This design lessens maintenance cost and simplifies replacement if there is any failure
- Optical glass lens with special design to have less light output loss (light transmission≥93%) and symmetric beam patter

Specification

Product Name	Saturn HB-400	IP Protection	IP54
Rated Power	400W	Dimension	146x386mm, 208x386mm with Hook
Luminous Efficiency	100-110Lm/W	Installation	Rigid Mount / with Hook
Luminous Flux	≥44000Lm	Replacement	1000W HID
Color Temp.	Cool white 6500K (4000K,5000K Option)	Material	Extrusion aluminum 6063
CRI	≥80	Lens Material	Optical glass
Beam Angle	45°, 65°, 85°, 120°	Lens Transmission	≥93%
Input Voltage	AC 170-250V	Weight	9.64 KG
Frequency	50/60Hz	Operating Temp.	-25°C to 45°C
Power Factor	≥0.95	Operating Humi.	10% to 90%
Power Efficiency	85%-90%	Certificate	CE, RoHS, TISI
Output Current	1.818A	Life Span	≥50000Hrs.
Harmonic (THD)	≤7%	Warranty	3 Years

Remark: The information contained in this document is subject to change without notice.



NEX Office

Singapore

50 Raffles Place, #37-00 Singapore Land
Tower 048623 Singapore
Tel.: (+65) 6829 7014 Fax.: (+65) 6829 707

Email: info@nexledtec.com www.nexledtec.com

Taiwan

4F, No.105 Zhongcheng Rd., Tucheng Distric,
New Taipei City 23674 Taiwan
Tel.: 886-2-22697815 Fax.: 886-2-22697807

Thailand

Q House Lumpini, 1 South Sathorn Rd., 27F,
Tungmahamek, Sathorn, Bangkok 10120 Thailand
Tel.&Fax.: +662 938 3672