




Dimension



Features

- High Color Rendering Index(CRI).
- Perfect low energy replacement for the Halogen Lamp.
- Bridge design makes it anti-glare and eye friendly.
- Energy saving up to 80% compared with traditional light.

Specification

General Informations	
Product name	NEX Enova SP-05 GU5.3
Rated Power	5W
Luminous Flux	215 lumen
Color Temp.	Warm white (2700K,3000K±300) Natural white (4000K±400)
CRI (Ra)	82 (92 Optional)
Beam Angle	12D,24D,36D
Reflector Type	MR16
Lamp Base	GU5.3
IP Protection	IP20
Dimensions	Ø50 x H50 mm
Housing Material	Aluminum
Housing Color	Aluminum color
Operating Temp.	-30°C to 40°C
Operating Humi.	10% to 90%
Lifespan(L70)	30000 Hrs.
Warranty	3 Years*

Electrical Informations	
Input voltage	AC12V,AC220-240V
Frequency.	50/60Hz
Power Factor	>0.9
Dimmable	Triac
Certificates & Test reports	
Certificates	CE,RoHS
Test reports	LM80/ TM21

Remark: The information contained in this document is subject to change without notice.
* 18Hrs/Day

CE RoHS

NEX Office & Showroom

Sookkamol Ratchada Building 2Floor,
410/17-23 Ratchadaphisek Rd., Samsennok,
Huay Kwang, Bangkok 10310, THAILAND


Tel. +662 204 7565
Fax. +662 938 3672
Email: info@nexledtech.com

www.nexledtech.com
www.nexinnotech.com

Ref. NEX Enova SP-XX V190531-2



Dimension



Features

- High Color Rendering Index(CRI).
- Perfect low energy replacement for the Halogen Lamp.
- Bridge design makes it anti-glare and eye friendly.
- Energy saving up to 80% compared with traditional light.

Specification

General Informations	
Product name	NEX Enova SP-07 GU5.3
Rated Power	7W
Luminous Flux	300 lumen
Color Temp.	Warm white (2700K,3000K±300) Natural white (4000K±400)
CRI (Ra)	82 (92 Optional)
Beam Angle	12D,24D,36D
Reflector Type	MR16
Lamp Base	GU5.3
IP Protection	IP20
Dimensions	Ø50 x H50 mm
Housing Material	Aluminum
Housing Color	Aluminum color
Operating Temp.	-30°C to 40°C
Operating Humi.	10% to 90%
Lifespan(L70)	30000 Hrs.
Warranty	3 Years*

Electrical Informations	
Input voltage	DC12V,AC220-240V
Frequency.	50/60Hz
Power Factor	>0.9
Dimmable	Triac
Certificates & Test reports	
Certificates	CE,RoHS
Test reports	LM80/ TM21

Remark: The information contained in this document is subject to change without notice.
* 18Hrs/Day

CE RoHS

NEX Office & Showroom


Sookkamol Ratchada Building 2Floor,
410/17-23 Ratchadaphisek Rd., Samsennok,
Huay Kwang, Bangkok 10310, THAILAND

Tel. +662 204 7565
Fax. +662 938 3672
Email: info@nexledtech.com

www.nexledtech.com
www.nexinnotech.com

Ref. NEX Enova SP-XX V190531-2

Dimension



Features

- High Color Rendering Index(CRI).
- Perfect low energy replacement for the Halogen Lamp.
- Bridge design makes it anti-glare and eye friendly.
- Energy saving up to 80% compared with traditional light.

Specification

General Informations	
Product Name	NEX Enova SP-05 GU10
Rated Power	5W
Luminous Flux	215 lumen
Color Temp.	Warm white (2700K,3000K±300) Natural white (4000K±400)
CRI (Ra)	82 (92 Optional)
Beam Angle	12D,24D,36D
Reflector Type	MR16
Lamp Base	GU10
IP Protection	IP20
Dimensions	Ø50 x H58 mm
Housing Material	Aluminum
Housing Color	Aluminum color
Operating Temp.	-30°C to 40°C
Operating Humi.	10% to 90%
Lifespan(L70)	30000 Hrs.
Warranty	3 Years*

Electrical Informations	
Input voltage	AC170-250V
Frequency.	50/60Hz
Dimmable	Triac
Power Factor	>0.9
Certificates & Test reports	
Certificates	CE,RoHS,TISI
Test reports	LM80/TM21

Remark: The information contained in this document is subject to change without notice.
* 18Hrs/Day



NEX Office & Showroom


Sookkamol Ratchada Building 2Floor,
410/17-23 Ratchadaphisek Rd., Samsennok,
Huay Kwang, Bangkok 10310, THAILAND

Tel. +662 204 7565
Fax. +662 938 3672
Email: info@nexledtech.com

www.nexledtech.com
www.nexinnotech.com



Dimension



Features

- High Color Rendering Index(CRI).
- Perfect low energy replacement for the Halogen Lamp.
- Bridge design makes it anti-glare and eye friendly.
- Energy saving up to 80% compared with traditional light.

Specification

General Informations	
Product Name	NEX Enova SP-07 GU10
Rated Power	7W
Luminous Flux	300 lumen
Color Temp.	Warm white (2700K,3000K±300) Natural white (4000K±400)
CRI (Ra)	82 (92 Optional)
Beam Angle	12D,24D,36D
Reflector Type	MR16
Lamp Base	GU10
IP Protection	IP20
Dimensions	Ø50 x H63 mm
Housing Material	Aluminum
Housing Color	Aluminum color
Operating Temp.	-30°C to 40°C
Operating Humi.	10% to 90%
Lifespan(L70)	30000 Hrs.
Warranty	3 Years*

Electrical Informations	
Input voltage	AC170-250V
Frequency.	50/60Hz
Dimmable	Triac
Power Factor	>0.9
Certificates & Test reports	
Certificates	CE,RoHS,TISI
Test reports	LM80/TM21

Remark: The information contained in this document is subject to change without notice.
* 18Hrs/Day



NEX Office & Showroom

Sookkamol Ratchada Building 2Floor,
410/17-23 Ratchadaphisek Rd., Samsennok,
Huay Kwang, Bangkok 10310, THAILAND

Tel. +662 204 7565
Fax. +662 938 3672
Email: info@nexledtech.com

www.nexledtech.com
www.nexinnotech.com