

NEX Illumi Spotlight RGBw



45W
Wireless
DMX

Features

Use receive standard DMX512 data transmission, It can be transmit the online data between light and light! This wireless dmx512 sending card use the 2.4G 2.4G Global open ISM band, Efficient GFSK modulation, 126 channel automatic frequency hopping communication design, anti-interference ability.



Specification

Model	SP-45
Product Code	SP-45RGBw
Power Consumption	45W
LED Sourc	9LEDx4W (4in1)
Input Voltage	AC110V-240V
Frequency	50-60Hz
Control Signal	DMX512
Control Channels	8 Channels
Wireless	Built-in 2.4G
Battery	Built-in
Standby Time	4-5 Hours
Weight	3.8Kg
Warranty	2 Years

Remark: The information contained in this document is subject to change without notice.

NEX Office

Singapore

50 Raffles Place, #37-00 Singapore Land
Tower 048623 Singapore
Tel.: (+65) 6829 7014 Fax.: (+65) 6829 707

Email: info@nexledtec.com www.nexledtec.com

Taiwan

4F, No.105 Zhongcheng Rd., Tucheng Distric,
New Taipei City 23674 Taiwan
Tel.: 886-2-22697815 Fax.: 886-2-22697807

Thailand

Q House Lumpini, 1 South Sathorn Rd., 27F,
Tungmahamek, Sathorn, Bangkok 10120 Thailand
Tel.&Fax.: +662 938 3672

Ref. NX-C-Follow-Light-AW2600-V1.0-2013