



≥3000Lm


CRI≥80

PF≥0.95

1200mm

Feature

- High light efficiency ≥ 150 Lm/w
- High Color Rendering Index (CRI) ≥ 80
- High Power Factor (PF) ≥ 0.95
- Longer life span ≥ 50000 hrs.
- Beam Angle 180 degree, perfect lighting effect and best color uniform



Dimension

Specification

Product Name	Illumi Pro T8-20	Dimension	30x1198mm
Rated Power	20W	Base Lamp	G13
Lighting Efficiency	≥ 150 Lm/W	Replacement	36W Fluorescent tube
Luminous Flux	≥ 3000 Lm	Material	Aluminum & PC cover
Color Temp.	Warm white (2700 $\pm$ 300K) Natural white (4500 $\pm$ 400K) Cool white (6500 $\pm$ 500K)	Cover Material	Frosted
CRI	≥ 80	Weight	360g
Beam Angle	180°	Operating Temp.	-20°C to 50°C
Input Voltage	AC 85-265V	Operating Humi.	10% to 90%
Frequency	50/60Hz	Certificate	CE, RoHS, TISI
Power Factor	≥ 0.95	Life span	≥ 50000 Hrs.
Harmonic (THD)	$\leq 10\%$	Warranty	3 Years*

Remark: The information contained in this document is subject to change without notice. *18Hrs/Day



NEX Office

Singapore

50 Raffles Place, #37-00 Singapore Land
Tower 048623 Singapore
Tel.: (+65) 6829 7014 Fax.: (+65) 6829 707

Email: info@nexledtec.com www.nexledtec.com

Taiwan

4F, No.105 Zhongcheng Rd., Tucheng Distric,
New Taipei City 23674 Taiwan
Tel.: 886-2-22697815 Fax.: 886-2-22697807

Thailand

Q House Lumpini, 1 South Sathorn Rd., 27F,
Tungmahamek, Sathorn, Bangkok 10120 Thailand
Tel.&Fax.: +662 938 3672