



LED T8 tube Infrared sensor



Dimension





Features

The Infrared sensor LED tube offers 100% brightness when there are people or cars passing through. After people or cars leave this place, the brightness will be dimmed to 10% so as to save power consumption. The LED tube light offers effective detection distance between 5 and 8 meters (relation by height).

Applications

Sensor informations

The Infrared sensor LED tube is has many uses in home lighting, office lighting, public place, such as galleries, courtyard, supermarket and much more.

Specifications

| = | |
|--|---|
| General Informations | |
| Product name Rated power LED type Luminous efficiency Luminous flux Color temp. | NEX Illumi T8-16 IR sensor 16W SMD ≥100 Lm/W ≥1,600 Lumen Warm white (2,700K+300) Natural white (4,000K+400) Cool white (6,500K+500) |
| CRI (Ra) Beam angle | ≥80 120 Deg. |
| IP protection | IP44 |
| Lamp base | G13 |
| Replacement | 36W traditional lamp |
| Dimensions | L590 x W30 x H35 mm |
| Weight | 210 g. |
| Housing material Operating temp. | Aluminum + PC -40°C to 45°C |
| Operating humi. | 10% to 90% |
| operating nami. | 1070 00 5070 |

50,000 Hrs.

3 Years*

| Sensor type Sensing distance | Infrared sensor 5-8 M (relation by height) |
|--|---|
| | |
| Electrical Informations | |
| | |
| Input voltage Frequency Power factor Total harmonic (THD) | AC 85-265V 50/60Hz ≥0.95 ≤15% |

Certificates & Test reports CE, RoHS, TISI Certificates LM80/TM21 **Test reports**

Remark: The information contained in this document is subject to change without notice.

CE RoHS (1955-255



DEX Office

Lifespan

Warranty

Thailand

Q House Lumpini, 1 South Sathorn Rd., 27F, Tungmahamek, Sathorn, Bangkok 10120 Thailand Tel.&Fax.: +662 938 3672

Taiwan

4F, No.105 Zhongcheng Rd., Tucheng Distric, New Taipei City 23674 Taiwan Tel.: 886-2-22697815 Fax.: 886-2-22697807

Singapore

50 Raffles Place, #37-00 Singapore Land Tower 048623 Singapore Tel.: (+65) 6829 7014 Fax.: (+65) 6829 707