



LED Wall Light









Features

The cover frame and the lamp body are made of aluminum alloy and molded through die-casting: the surface is treated by two processes of electrostatic dusting. The step cover is equipped with sandblasted fully toughened glass with woven design: Silica gel waterproof gaskets which are resistant to high temperature are installed under the cover: the protection class is IP55.Two kinds of light sources; LED and QT9 are optional for this product: electric appliances are installed internally. It is suitable for exterior corridor, passage way, wall footing, park and so on. This product is CE certified and all materials are in conformity with RoHS standard.



Specification

Model Illumi WL-04 **Rated Power** 3.5W **Luminous Flux** >250Lm Color Temp.

Warm white (3000±100K)

AC220-240V Input Voltage 50/60Hz Frequency Driver Include 45° **Beam Angle CRI** ≥80

IP Protection IP55

W150xH100xD97mm Dimension **Cut Out** W145xH85xD100mm Material Aluminum alloy Surface Color Gray color -20°C to 50°C Operating Temp.

10% to 90% Operating Humi. Certificate CE, RoHS

Life span ≥35000Hrs. Warranty 3 Years*

Remark: The information contained in this document is subject to change without notice. * 18Hrs/Day

DEX Office

Singapore

50 Raffles Place, #37-00 Singapore Land Tower 048623 Singapore Tel.: (+65) 6829 7014 Fax.: (+65) 6829 707

Taiwan

4F, No.105 Zhongcheng Rd., Tucheng Distric, New Taipei City 23674 Taiwan Tel.: 886-2-22697815 Fax.: 886-2-22697807

Email: info@nexledtec.com www.nexledtec.com

Thailand

Q House Lumpini, 1 South Sathorn Rd., 27F, Tungmahamek, Sathorn, Bangkok 10120 Thailand Tel.&Fax.: +662 938 3672