



Features

- Working Voltage: AC/DC24V, Constant current driver, No flash, fast response to achieve over-current, use of safety.
- High quality 316L Stainless Steel fixture with 316SS screws. Reasonable and modern design. Good structure for sending heat.
- One driver working low voltage power and DMX512 function.
- No waterproof glue to fill the light, easy maintain and replace freely.
- DMX512 controllable (1990 standard for DMX512)
- Rubber cable or UL rubber cable. One cable with 5wires/ 7wires.
- Waterproof IP68. Underwater or outdoor used.
- Beam angle chosen by clients' request, from 10°-90°.

Specifications

General Informations		Electrical Informations	
Product Name	NEX Aqua UL-48	Driver	Isolated driver
Rated Power	48W (16x3W)	Input Voltage	AC/DC 24V
Color Temp.	Single Color/ RGB	Control way	Auto color change or DMX512 controllable
Beam Angle	10D,30D,45D, 60D,90D Optional	Cable Wire	1 meter 3 wires or 5 wires/ 6 wires cable
IP Protection	IP68 Waterproof	Certificates & Test reports	
Dimensions	Ø175xH230mm	Certificates	CE, RoHS
Housing Material	316L Stainless Steel + Tempered glass	Test Reports	LM80/TM21
Rens Type	Transparent/Frosted Optional	Remark: The information contained in this document is subject to change without notice. * 18Hrs/Day	
Housing Color	Silver	CE RoHS	
Operating Temp.	-20°C to 55°C		
Operating Humi.	10% to 90%		
Lifespan	50000 Hrs.		
Warranty	2 Years*		