# **NEX**<sup>®</sup>Enova

## 25W LED Floodlight



#### Feature

- Citizen COB or Bridgelux Arrays adopted, delivering 140 to 160 lumen per watt, converting more power to light.
- Patented passive cooling solution to manage surface temperature rising of luminaire at 30°C, junction temperature of led chip controlled at 100°C.
- Optical glass led lens with a light transmission more than 99%, offering the least light output loss, special rectangle shape designed to have a symmetric beam patter.
- 50000 hours lifespan putting the luminaire replacement circle to 20 years.
- IP66 water and dust proof, and aluminium alloy fixture with corrosion resistant.
- Power factor at 0.9~0.99.
- Easiest installation and maintenance, each part is replaceable.
- 3 years warranty, 5years optional.
- CE, FCC, RoHS and TISI marked.

### Specifications

General Informations		Operating Humi.	10% to 90%
Product Name Rated Power	25W Citizen 1 Pcs. ≥140 lm/W iciency ≥92 lm/W	Lifespan Warranty	50000 Hrs. 3 Years*
LED Chip LED Quantity		Electrical Informations	
LED Efficacy Luminous Efficiency Luminous Flux Color Temp.		Input Voltage Frequency Output Current Power Factor	AC100-277V 50/60Hz 0.11A ≥0.99
CRI (Ra) Beam Angle	≥80 60Dx120D	Power Efficiency Total Harmonic (THDi)	
Lens Material Lens Light Transmissio	Optical glass n 99%	Surge Protection	2kA
IP Protection Replacement	IP65 (IP66 Optional) 70W HID	Certificates & Test reports	
Dimensions Weight Housing Material	L95xW118xD80 mm 1.32 Kg. Aluminum alloy	Certificates Test Reports	CE,RoHS,FCC,TISI LM80/TM21
Housing Color Operating Temp.		Remark: The information contained in this document is subject to change without notice. * 18Hrs/Day CEROHSFC	

#### **NEX** Office & Showroom

Sookkamol Ratchada Building 2Floor, 410/17-23 Ratchadaphisek Rd., Samsennok, Huay Kwang, Bangkok 10310, THAILAND Tel. +662 204 7565 Fax. +662 938 3672 Email: info@nexledtech.com www.nexledtech.com www.nexinnotech.com